



SYNTH-TECH XT SAE 5W-30

DATA SHEET

Description

PROFI-CAR SYNTH-TECH XT SAE 5W-30 is a high-performance low-friction engine oil for all suitable gasoline engines. It was specially developed for use in modern passenger car engines with and without turbochargers.

Specification

API SP

ILSAC GF-6A

Application recommendation

Baic	BYD	Changan
Chery	Daihatsu	Dongfeng
GAC	Geely	Genesis
Haval	Honda	Hongqi
Hyundai	Isuzu	JAC Motors
Jetour	Kia	Lexus
Mazda	Mitsubishi	Nissan
Proton	SAIC Motor	Ssangyong
Subaru	Suzuki	Toyota

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	857
Viscosity 40°C	DIN 51562-1	mm ² /s	62,10
Viscosity 100°C	DIN 51562-1	mm ² /s	10,5
Viscosity index	DIN ISO 2909		159
TBN	DIN ISO 3771	mgKOH/g	7,2
Pourpoint	DIN ISO 3016	°C	- 39
Flash point	DIN ISO 2592	°C	232

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**