



FS SAE 5W-30

DATA SHEET

Description

PROFI-CAR FS 5W-30 is a premium passenger car engine oil for certain gasoline (also hybrid), ethanol (up to E85), propane and natural gas engines. Mainly for Asian and American brands equipped with the latest engine technology. The composition of the oil minimizes the likelihood of premature ignition (LSPI). Extended oil change intervals are possible according to the manufacturer's instructions.

This product is not suitable for diesel engines!

Specification

API SP

ILSAC GF-6A

Application recommendation

Chrysler MS-6395	Daihatsu	Dexos1 Gen 3
Fiat 9.55535-CR1	Ford WSS-M2C 929-A	Ford WSS-M2C 946-A/-B1
Ford WSS-M2C 961-A	GM 6094M	Honda
Isuzu	Kia	Lexus
Mazda	Nissan	Subaru
Suzuki	Toyota	

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	848
Viscosity 40°C	DIN 51562-1	mm ² /s	60,9
Viscosity kin. 100°C	DIN 51562-1	mm ² /s	10,9
Viscosity index	DIN ISO 2909		171
TBN	DIN ISO 3771	mgKOH/g	8,0
Pourpoint	DIN ISO 3016	°C	-45
Flammable COC	DIN ISO 2592	°C	224

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**