0002013 / 14020 Date: 02/12/2024



## ECO-DRIVE FE SAE OW-20

### **DATA SHEET**

#### **Description**

ECO-DRIVE FE+ SAE 0W-20 can cope with all thermal and mechanical loads that can occur in modern car engines designed for fuel economy. Its high cleaning and dirt-carrying capacity ensures maximum engine cleanliness and optimum wear protection.

ECO-DRIVE FE+ SAE 0W-20 guarantees potential fuel savings and helps to protect the environment by reducing CO2 emissions.

ECO-DRIVE FE+ SAE 0W-20 is a year-round low-friction engine oil for passenger car engines for which Fuel Economy (FE) is prescribed or approved.

ECO-DRIVE FE+ SAE 0W-20 is fully compatible with the latest diesel particulate filters (DPF) and with the catalytic converters of gasoline engines.

#### **Specification**

ACEA C5/C6

API SP (RC)

ILSAC GF-6A

#### **Application recommendation**

 BMW-Longlife-17 FE+
 Chrysler MS-12145
 Fiat 9.55535-GSX

 Ford WSS-M2C947-B1
 Ford WSS-M2C962-A1
 GM DexosD

 Jaguar/ Land Rover STJLR 03-5006-16
 MB 229.71
 MB 229.72

Opel/Vauxhaul OV0401547 Volvo VCC RBS0-2AE

Product attributes			
Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m³	846
Viscosity 40°C	DIN 51562-1	mm²/s	41,9
Viscosity -35°C	DIN 51377	mPa*s	6050
Viscosity 100°C	DIN 51562-1	mm²/s	8,1
Viscosity index	DIN ISO 2909		172
TBN	DIN ISO 3771	mgKOH/g	7,6
Pourpoint	DIN ISO 3016	°C	-49
Flammable COC	DIN ISO 2592	°C	230

# powered by Quality.

PROFI-CAR MADE IN GERMANY

0002013 / 14020 Date: 02/12/2024



The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

