



ECO-DRIVE LONGLIFE 3 SAE 5W-30

DATA SHEET

Description

ECO-DRIVE LONGLIFE 3 SAE 5W-30 is a HC-synthetic high-performance low-friction engine oil for gasoline and diesel engines in passenger cars, with low sulphur, ash and phosphorus content (low SAPS). It has been developed for modern passenger car engines with the latest technology, in particular with diesel particulate filters and exhaust gas aftertreatment.

Specification

ACEA C3

Application recommendation

BMW LL-04

MB 229.51

Porsche C30

VW 504 00 / 507 00

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	852
Viscosity 40°C	DIN 51562-1	mm ² /s	70,1
Viscosity 100°C	DIN 51562-1	mm ² /s	11,9
Viscosity index	DIN ISO 2909		167
TBN	DIN ISO 3771	mgKOH/g	6,2
Pourpoint	DIN ISO 3016	°C	-45
Flammable COC	DIN ISO 2592	°C	230

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**