



STOP & GO SAE 5W-30

DATA SHEET

Description

STOP & GO SAE 5W-30 is a HC-synthetic high-performance low-friction engine oil for passenger cars with modern exhaust gas aftertreatment and extended oil change intervals. Can be used in all suitable gasoline and diesel engines. Especially for diesel engines with DPF systems (low SAPS).

Specification

ACEA C3

API SN/CF

Application recommendation

BMW LL-04

GM dexos 2

MB 226.5

MB 229.51 / 229.52

Renault RN 0700 / 0710

VW 502 00 / 505 00 / 505 01

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	854
Viscosity 40°C	DIN 51562-1	mm ² /s	70,4
Viscosity 100°C	DIN 51562-1	mm ² /s	11,9
Viscosity index	DIN ISO 2909		167
Pourpoint	DIN ISO 3016	°C	-42
Flammable COC	DIN ISO 2592	°C	230

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**