



EVOLUTION RT SAE 10W-60

DATA SHEET

Description

EVOLUTION RT SAE 10W-60 is a modern and universally applicable passenger car engine oil. Suitable for a wide range of vehicles such as Alfa Romeo, Aston Martin, Lancia, Lotus, Maserati.

Please observe the manufacturer's instructions!

Specification

ACEA A3/B3, A3/B4

API SN/CF

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m ³	830 - 870
Viscosity dyn. -25°C	ASTM D5293	mPa*s	max. 7.000
Viscosity kin. 100°C	ASTM D7279	mm ² /s	23,3 - 24,7
Viscosity index	ASTM D2270		min. 170
TBN	ASTM D2896	mgKOH/g	7,0 - 9,0
Pourpoint	ASTM D7346	°C	max. -33
Flammable COC	DIN ISO 2592	°C	min. 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**