



EVOLUTION XT SAE 10W-30

DATA SHEET

Description

EVOLUTION XT 10W-30 is a semi-synthetic high-performance low-friction engine oil. This oil is recommended for passenger car gasoline and diesel engines, including turbo and catalytic converter versions.

Specification

ACEA A3/B4

API SN/CF

Application recommendation

Chrysler MS-6395	Daewoo	Daihatsu
Fiat 9.55535-CR1	GM 6094 M	Honda
Hyundai	Isuzu	Kia
Lexus	Mazda	Mitsubishi
Nissan	SsangYong	Subaru
Suzuki	Toyota	

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	860
Viscosity 40°C	DIN 51562-1	mm ² /s	61,9
Viscosity 100°C	DIN 51562-1	mm ² /s	10,3
Viscosity index	DIN ISO 2909		154
TBN	DIN ISO 3771	mgKOH/g	10,5
Pourpoint	DIN ISO 3016	°C	-36
Flammable COC	DIN ISO 2592	°C	232

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**