



PERFORMANCE SAE 15W-40

DATA SHEET

Description

performance SAE 15W-40 is a mineral oil-based high-performance universal engine oil. It is used in highly stressed passenger car diesel and gasoline engines, with and without turbocharging.

Specification

ACEA A3/B4

API SL/CF

Application recommendation

MB 229.1

VW 505 00

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	871
Viscosity 40°C	DIN 51562-1	mm ² /s	103
Viscosity 100°C	DIN 51562-1	mm ² /s	14
Viscosity index	DIN ISO 2909		138
TBN	DIN ISO 3771	mgKOH/g	10,5
Pourpoint	DIN ISO 3016	°C	-36
Flammable COC	DIN ISO 2592	°C	224

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**