



# PERFORMANCE SAE 20W-50

## DATA SHEET

### Description

performance SAE 20W-50 is a mineral oil-based high-performance universal engine oil. It is used in highly stressed commercial vehicle and passenger car diesel engines, as well as in gasoline engines.

### Specification

ACEA A3/B4

API SL/CF

### Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m <sup>3</sup>	885
Viscosity 40°C	DIN 51562-1	mm <sup>2</sup> /s	157
Viscosity 100°C	DIN 51562-1	mm <sup>2</sup> /s	18,4
Viscosity index	DIN ISO 2909		132
TBN	DIN ISO 3771	mgKOH/g	8,7
Pourpoint	DIN ISO 3016	°C	-36
Flammable COC	DIN ISO 2592	°C	236

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

**powered by Quality.**



PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)  
**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**