



SPEED SAE 15W-40

DATA SHEET

Description

SPEED SAE 15W-40 is a mineral oil-based universal engine oil of viscosity class SAE 15W-40 with high wear and corrosion protection.

SPEED SAE 15W-40 is suitable for diesel and gasoline engines in accordance with the manufacturer's specifications. The SAE class 15W-40 ensures year-round use in Central Europe.

Specification

API SF/CD

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	880
Viscosity 40°C	DIN ISO 3104	mm ² /s	96
Viscosity at -20°C	ASTM D5293	mPa*s	5460
Viscosity 100°C	DIN ISO 3104	mm ² /s	13,3
Viscosity index	DIN ISO 2909		144
TBN	DIN ISO 3771	mgKOH/g	6,0
Pourpoint	DIN ISO 3016	°C	-39
Flammable COC	DIN ISO 2592	°C	232

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.



PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**