



# SPEED SAE 20W-50

## DATA SHEET

### Description

SPEED SAE 20W-50 is a mineral oil-based universal engine oil of viscosity class SAE 20W-50 with high wear and corrosion protection.

SPEED SAE 20W-50 is suitable for diesel and gasoline engines in accordance with the manufacturer's specifications. The SAE class 20W-50 ensures year-round use in Central Europe.

### Specification

API SF/CD

### Product attributes

| Attribute       | Method       | Unit               | Value |
|-----------------|--------------|--------------------|-------|
| Density 15°C    | DIN 51757    | Kg/m <sup>3</sup>  | 884   |
| Viscosity 40°C  | DIN ISO 3104 | mm <sup>2</sup> /s | 152   |
| Viscosity 100°C | DIN ISO 3104 | mm <sup>2</sup> /s | 16,72 |
| Viscosity index | DIN ISO 2909 |                    | 118   |
| Pourpoint       | DIN ISO 3016 | °C                 | -27   |
| Flammable COC   | DIN ISO 2592 | °C                 | 254   |

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

**powered by Quality.**



PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)  
**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**