



# DEX-TECH III-H

## DATA SHEET

### Description

DEXRON III is a high-quality automatic transmission oil that meets the Dexron III-H specification. The product is also suitable for use in the Dexron II range. This oil has very good oxidation stability and a very low flow point.

Observe the manufacturer's instructions!

### Application recommendation

Allison C-4	Caterpillar TO-2	Ford Mercon
GM Dexron III-H	MAN 339 Typ Z1/V1	MB 236.1 / 236.5 / 236.6 / 236.7
Voith H55.6335.3x (G607)	Volvo 97341	ZF TE-ML 03D, 04D, 09/11/14A,17C

### Product attributes

Attribute	Method	Unit	Value
Colour			rot
Density 15°C	DIN 51757	Kg/m <sup>3</sup>	860
Viscosity 40°C	DIN 51562-1	mm <sup>2</sup> /s	36
Viscosity 100°C	DIN 51562-1	mm <sup>2</sup> /s	7,5
Viscosity index	DIN ISO 2909		176
Pourpoint	DIN ISO 3016	°C	-48
Flammable COC	DIN ISO 2592	°C	176

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**



PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)  
**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**