



DEX-TECH ATF DCT

DATA SHEET

Description

DEX-TECH ATF DCT is a state-of-the-art automatic transmission fluid for dual clutch transmissions (DCT).

Not suitable for use in stepped automatic transmissions or CVT transmissions.

Please observe the manufacturer's instructions!

Application recommendation

BMW 6-speed DCT	BMW 83 22 0397 244	BMW 83 22 2 147 477
BMW 83 22 2 148 578	BMW 83 22 2 148 579	BMW 83 22 2 446 673
BMW DCTF-1 (83 220 440 214)	BMW DCTF-1+ / DCTF-2	BMW Drivelogic 7-speed (Getrag)
BMW MTF LT-5 (83 22 2167 666)	Borg Warner	Bugatti Veyron
BYD DCTs, Q/BYD-A1909.0058-2013	Changan DCTF	Chrysler Powershift 6-speed (Getrag) 6 8044345 EA&GA
Citroen/Peugeot 6DCT451 (PSA 9734. S2)	Eaton PS-278	Ferrari 7-speed (Getrag)
Ferrari TF DCT-F3	Fiat 9.55550-MZ6	Ford F-DC, part # KU7J M2C218AA
Ford WSS-M2C218-A1	Ford/Nissan Powershift 6-Speed (GFT)	Ford/Nissan WSS-M2C-200-D2
Ford/Nissan WSS-M2C936A part#149 0763/1490761	Ford/Nissan XT-11-QDC	Geely 7 speed
MB 236.21 / 236.24 / 236.25	MB 239.21	Mitsubishi Dia-Queen SSTF-I
Mitsubishi TC-SST 6-Speed (GFT)	Porsche 000 043 20	Porsche 000 043 210 44
Porsche 000 043 305 13	Porsche 043 207 29	Porsche 043 207 30
Porsche 971 094 307 02A	Porsche 999 917 080 00	Porsche 999 917 080 01
Renault BOT 450	Renault EDC 6-Speed (Getrag)	Renault EDC-7 / 77 11 785 243 (DW5)
Volvo 1161838, 1161839	Volvo Powershift 6-Speed (GFT)	VW (Audi, Seat, Skoda) 6-speed
VW / Audi G 052 512	VW / Audi G 055 529 (TL 52 529-C)	VW 7 speed VW (Audi, Seat, Skoda)
VW G 052 536 / G 055 536	VW G 052 182 A2/A6 (fluid) / TL 521 82 (spec)	VW G 052 529 A2/A6 (fluid)
ZF Lifeguard Fluid 8.2 (ZF 0671.090.54 5)	VW Golf GTE DQ400E	VW TL 52 529 (spec)
	ZF TE-ML 11 (ZF004743)	

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of PROFI-TECH GmbH



Product attributes

Attribute	Method	Unit	Value
Colour			farblos
Density 15°C	DIN 51757	Kg/m ³	847
Viscosity 40°C	DIN 51562-1	mm ² /s	36
Viscosity 100°C	DIN 51562-1	mm ² /s	7
Viscosity index	DIN ISO 2909		158
Pourpoint	DIN ISO 3016	°C	-45
Flammable COC	DIN ISO 2592	°C	> 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**