



ECO-LINER SAE 5W-30

DATA SHEET

Description

ECO-LINER SAE 5W-30 is a special HC-synthesis LONGLIFE truck engine oil with fuel economy properties and extended oil change intervals. Can be used in all suitable gasoline, diesel or LPG engines. Especially for DPF systems. Turbo and catalyst tested.

Specification

ACEA E6/E7/E9

API CK-4/SN

JASO DH-2

Application recommendation

Caterpillar ECF-3	Cummins CES 20086	DAF Extended Drain
Detroit Diesel DDC 93K222	Deutz DQC IV-18 LA	DTFR 15C100 (MB 228.31)
DTFR 15C110 (MB 228.51)	DTFR 15C120 (MB 228.52)	Ford WSS M2C213-A1
Iveco 18-1804 TLS E9	Mack EOS 4.5	MAN M3677, M3775, M3271-1, M3477
MTU TYPE 3.1	Renault RLD-3	Volvo VDS-4.5

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m ³	850 - 880
Viscosity dyn. -30°C	ASTM D5293	mPa*s	max. 6.600
Viscosity kin. 100°C	ASTM D7279	mm ² /s	11,0 - 12,4
Viscosity index	ASTM D2270		min. 155
TBN	ASTM D2896	mgKOH/g	9,3 - 11,7
Pourpoint	ASTM D7346	°C	max. -39
Flammable COC	DIN ISO 2592	°C	min. 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**