



# ACTRON SAE 10W-40

## DATA SHEET

### Description

ACTRON SAE 10W-40 is a special HC-synthesis LONGLIFE truck engine oil with fuel economy properties and extended oil change intervals. Can be used in all suitable gasoline, diesel or LPG engines. Turbo and catalyst tested.

### Specification

ACEA E4/E7

API CI-4

### Application recommendation

Deutz DQC IV-10

DTFR 15B120 (MB 228.5)

Mack EO-N

MAN M3277, M3377

MTU TYPE 3

Renault RLD-2

Volvo VDS-3

### Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m <sup>3</sup>	840 - 880
Viscosity dyn. -25°C	ASTM D5293	mPa*s	max. 7.000
Viscosity kin. 100°C	ASTM D7279	mm <sup>2</sup> /s	13,3 - 14,7
Viscosity index	ASTM D2270		min. 148
TBN	ASTM D2896	mgKOH/g	10,8 - 13,2
Pourpoint	ASTM D7346	°C	max. -33
Flammable COC	DIN ISO 2592	°C	min. 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

**PROFI-CAR**  
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)  
**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**