



DIESEL-POWER-TRUCK TURBO SAE

DATA SHEET

Description

DIESEL-POWER-TRUCK TURBO SAE 20W-50 is a premium engine oil with synthetic additives. Can be used in all suitable gasoline, diesel, or LPG engines. Turbo and catalyst tested.

Specification

ACEA A3/B4/E7

API CI-4/SL

JASO DH-1-17

Application recommendation

Detroit Diesel DDC 93K215

Deutz DQC II-10

DTFR 15B110 (MB 228.3)

Global DHD-1

Mack EO-N

MAN M3275-1

Renault RLD-2

Volvo VDS-3

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m ³	860 - 890
Viscosity dyn. -15°C	DIN 51377	mPa*s	max. 9.500
Viscosity kin. 100°C	DIN 51562-1	mm ² /s	16,2 - 17,8
Viscosity index	DIN ISO 2909		min. 135
TBN	DIN ISO 3771	mgKOH/g	10 - 12
Pourpoint	DIN ISO 3016	°C	max. -36
Flammable COC	DIN ISO 2592	°C	min. 210

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**