



DIESEL-POWER-TRUCK MONO-G

SAE 50

DATA SHEET

Description

DIESEL-POWER-TRUCK MONO-G SAE 50 is a premium engine oil. Can be used in all suitable gasoline and diesel engines.

Specification

API CF-4/SJ

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m ³	880 - 920
Viscosity kin. 100°C	ASTM D7279	mm ² /s	19,8 - 21,2
TBN	DIN ISO 2592	mgKOH/g	7,3 - 9,3
Pourpoint	ASTM D7346	°C	max. -15
Flammable COC	DIN ISO 2592	°C	min. 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**