PERFORMANCE 2T

DATA SHEET

Description

Two-stroke engine oil based on mineral oil.
Good protection against rust, corrosion and wear.
Stable lubricating film prevents piston jamming and seizure.
Provides protection against deposits and spark plug bridge formation.
For use in systems with separate and mixed lubrication.
Environmentally friendly due to low smoke emission.

performance 2T is a universal two-stroke engine oil for air- and water-cooled two-stroke engines in mopeds, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.
Observe manufacturer's instructions.

Specification

API TC

ISO-L-EGD

JASO FB

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m³	878
Viscosity 40°C	DIN 51562-1	mm²/s	63,6
Viscosity 100°C	DIN 51562-1	mm²/s	8,6
Viscosity index	DIN ISO 2909		108
Pourpoint	ASTM D7346	°C	-24
Flammable COC	DIN ISO 2592	°C	141

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of PROFI-TECH GmbH