



SYNTH-TECH 4T SAE 5W-50

DATA SHEET

Description

High-performance engine oil for 4-stroke motorcycle engines.
Exceptional wear protection
Outstanding shear stability
Optimized friction properties
Outstanding low-temperature behavior
Excellent detergent/dispersant behavior
Also suitable for wet clutches
Effective rust and corrosion protection
For maximum engine protection

SYNTH-TECH 4T SAE 5W-50 is specially recommended for the lubrication of 4-stroke motorcycle engines in high-performance motorcycles, even under extreme operating conditions (race track and road).
Observe manufacturer's instructions.

Specification

API SN
JASO MA2

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	863
Viscosity 40°C	DIN 51562-1	mm ² /s	108
Viscosity dyn. -30°C	DIN 51377	mPa*s	5770
Viscosity 100°C	DIN 51562-1	mm ² /s	18
Viscosity index	DIN ISO 2909		185
TBN	DIN ISO 3771	mgKOH/g	10,5
Pourpoint	DIN ISO 3016	°C	-39
Flammable COC	DIN ISO 2592	°C	226

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**