



ULTRA PROTECT 5, 250 ML

DATA SHEET

Description

PROFI-CAR ULTRA PROTECT 5 BENZIN is a fuel additive which replaces 5 conventional additives.

Characteristics

Cleans and protects the complete gasoline-fuel system and binds water in the tank.

Cleans and protects the injectors.

Cleans and protects valves and valve seats.

Increases the octane number.

Cleans and protects the exhaust system.

Usage

Add to the tank filling after refueling. Can content is sufficient for about 60 liters of fuel.

Application areas

Suitable for all gasoline engines.

Product attributes

Attribute	Method	Unit	Value
Density 20°C		Kg/m ³	803
Freezing point		°C	-22
Boiling range		°C	175 - 230
Flash point		°C	62
Ignition temperature		°C	> 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**