



ULTRA PROTECT 5 DIESEL, 250 ML

DATA SHEET

Description

ULTRA PROTECT 5 DIESEL is a fuel additive that replaces 5 conventional additives.

Characteristics

Cleans and protects the entire system from the tank to the combustion chamber.

Improves the storage stability of the diesel.

Prevents deposits in the injection system and on the injectors.

Increases the cetane number.

Reduces soot particles through afterburning in DPF filters.

Usage

Add to the tank filling. Do not completely empty the tank. Can content is sufficient for approx. 60 liters of fuel.

Application areas

Suitable for all diesel engines.

Product attributes

Attribute	Method	Unit	Value
Density 20°C		Kg/m ³	815
Flash point		°C	63
Boiling range		°C	180 - 250
Ignition temperature		°C	> 200

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**