



FD ECO SAE 5W-20

DATA SHEET

Description

FD ECO 5W-20 is a HC-synthetic high-performance low-friction engine oil of the latest technology especially for modern Ford EcoBoost engines. Outstanding cold start behavior ensures optimum lubrication reliability in the cold running phase. The special additive improves the protection of the catalytic converter. Guarantees maximum engine cleanliness and optimum wear protection. The exceptional product stability enables extended oil change intervals.

FD ECO 5W-20 guarantees fuel savings of up to savings potential of up to 3% and helps to protect the environment by reducing CO2 emissions.

Application notes:

FD ECO 5W-20 has been specially developed for the latest Ford EcoBoost engines.

Observe manufacturer's instructions.

Specification

ACEA C5

API SN (RC) / CF

ILSAC GF-5

Application recommendation

Chrysler MS-6395

Fiat 9.955535-CR1

Ford WSS-M2C912-A

Ford WSS-M2C913-A/B/C

Ford WSS-M2C925-B

Ford WSS-M2C948-A/B

Jaguar/ Land Rover STJLR.03.5004

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	846
Viscosity 40°C	DIN 51562-1	mm ² /s	44,75
Viscosity 100°C	DIN 51562-1	mm ² /s	8,27
Viscosity index	DIN ISO 2909		162
Pourpoint	DIN ISO 3016	°C	-42
Flammable COC	DIN ISO 2592	°C	226

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.



PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**