SCOOTER 4T SAE 5W-40

DATA SHEET

Description

SCOOTER 4T 5W-40 is a high-performance engine oil for 4-stroke motorcycle engines.

SCOOTER 4T 5W-40 is recommended for the lubrication of 4-stroke motorcycle engines
motorcycle engines with air or water cooling, both in touring operation
on the road or off-road.
Observe manufacturer's instructions.

Specification

ACEA A3

API SN PLUS

JASO MA2

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m³	852
Viscosity 40°C	DIN 51562-1	mm²/s	88,6
Viscosity dyn. -30°C	DIN 51377	mPa*s	6130
Viscosity 100°C	DIN 51562-1	mm²/s	14,7
Viscosity index	DIN ISO 2909		174
TBN	DIN ISO 3771	mgKOH/g	11,1
Pourpoint	DIN ISO 3016	°C	-42
Flammable COC	DIN ISO 2592	°C	224

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of PROFI-TECH GmbH