



SYNTH-TECH 4T SAE 20W-50 H.D.

DATA SHEET

Description

SYNTH-TECH 4T SAE 20W-50 HARLEY-DAVIDSON is a high-performance engine oil for 4-stroke motorcycle engines with the following properties:

- High wear protection
- Very good shear stability
- Optimized friction properties
- Excellent detergent/dispersant behavior
- Also suitable for wet clutches
- Effective rust and corrosion protection
- For optimum engine protection

SYNTH-TECH 4T SAE 20W-50 HARLEY-DAVIDSON is specially recommended for the lubrication of 4-stroke motorcycle engines in motorcycles, even under demanding operating conditions.
Observe manufacturer's instructions.

Specification

API SN

JASO MA/MA2

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	883
Viscosity 40°C	DIN 51562-1	mm ² /s	175
Viscosity 100°C	DIN 51562-1	mm ² /s	19,5
Viscosity index	DIN ISO 2909		128
TBN	DIN ISO 3771	mgKOH/g	7,5
Pourpoint	DIN ISO 3016	°C	-21
Flammable COC	DIN ISO 2592	°C	>195

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**