



EXTRA-SYNTH SAE 15W-40

DATA SHEET

Description

EXTRA-SYNTH SAE 15W-40 is a semi-synthetic high-performance low-friction engine oil. This oil is recommended for passenger car gasoline and diesel engines, including turbo and catalytic converter versions.

Specification

ACEA A3/B4

API SN/CF

Application recommendation

MB 229.1

VW 505 00

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN 51757	Kg/m ³	871
Viscosity 40°C	DIN 51562-1	mm ² /s	103
Viscosity 100°C	DIN 51562-1	mm ² /s	14
Viscosity index	DIN ISO 2909		138
TBN	DIN ISO 3771	mgKOH/g	10,5
Pourpoint	DIN ISO 3016	°C	-36
Flammable COC	DIN ISO 2592	°C	224

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

powered by Quality.



PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**