PROFI-CAR

ALLROUND SAE 5W-30

DATA SHEET

Description

ALLROUND SAE 5W-30 offers outstanding performance and reliability thanks to advanced synthetic technology and innovative additives.
Versatile and perfectly suited for modern gasoline and diesel engines, including turbo models and engines with exhaust aftertreatment systems (e.g. DPF).

ATTENTION: Observe manufacturer's instructions.

Specification

ACEA C2/C3

API SQ (RC); API CF

ILSAC GF-6A

Application recommendation

BMW Longlife-04

Chrysler MS-6395 / MS-13340

Ford WSS-M2C917-A

Jaguar Land STJLR.03.5007

MB 229.31

OPEL GM-LL-A-025

OPEL OV 040 1547-G30

PSA B71 2297

VW 504 00 / 507 00

CHINESE Standard GB VI A

Fiat 9.55535-S1

GM dexos 2

KIA SFU

MB 229.51

OPEL GM-LL-B-025

Porsche C30

RENAULT RN0700 / RN0710

VW 505 00 / 505 01

CHINESE Standard GB VI B

Fiat 9.55535-S3

GM dexos1 Gen 3

MB 226.52

MB 229.52

OPEL OV 040 1547-D30

PSA B71 2290-2014

VW 502 00 / 503 01

Product attributes

Attribute	Method	Unit	Value
Density 15°C	DIN EN ISO 12185	Kg/m³	854
Viscosity 40°C		mm²/s	73,5
Viscosity kin. 100°C		mm²/s	11,9
TBN	ASTM D2896	mgKOH/g	8,3
Pourpoint	DIN ISO 3016	°C	-33

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place. The given data are typical data. Please observe instructions! Our data sheets and prints should advise in all conscience. The content is regarding to treatment and application an unenforceable obligation as we have no bearing on it. Modifications which result in improvement are reserved.

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of PROFI-TECH GmbH