

PC VENTIL-CLEANER

Page: 1

Compilation date: 17.11.2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PC VENTIL-CLEANER (UFI:U57C-G5GX-P003-PF4A)

Product code: 60022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaner corrosion protection additiv liquid

1.3. Details of the supplier of the safety data sheet

Company name: PROFI-TECH GmbH

Otto-Lilienthal-Strasse 2

Friedrichshafen

88046

Germany

Tel: +49 7541 402860

Fax: +49 7541 4028699

Email: info@profi-tech.com

1.4. Emergency telephone number

Emergency tel: 24-hour emergency contact number out side USA/Canada: + 49 70024112112 (PRT)

24-hour emergency contact number in side USA/Canada: +11 49 70024112112 (PRT)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Aquatic Chronic 3: H412; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. May be fatal if swallowed and

enters airways. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways. H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS08: Health hazard



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P273: Avoid release to the environment.



PC VENTIL-CLEANER

Page: 2

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBON MIX C10-C13, <0,1% BENZENE - REACH registered number(s): 01-2119457273-39-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
918-481-9	64742-48-9	-	Asp. Tox. 1: H304; -: EUH066	70-90%

KEROSINE - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. - REACH registered number(s): 01 -2119510128-50-0000

265-198-5	64742-94-5	-	Asp. Tox. 1: H304; Aquatic Chronic 2:	1-10%
			H411	

2-ETHYL-1-HEXANOL - REACH registered number(s): 01-2119487289-20

203-234-3	104-76-7	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H335	

Non-classified ingredients:

HYDROCARBONS, C11-14,N-ALKANES, ISOALKANES, CYCLICS, <2%AROMATICS [DISTILLATES (PETROLEUM), HYDROTREATED LIGHT] - REACH registered number(s): 01-2119456620-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-149-8	64742-47-8	-	Asp. Tox. 1: H304; -: EUH066	<1%

1,2,4-TRIMETHYLBENZENE - REACH registered number(s): COMPLIANT

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332;	<1%
			Eye Irrit. 2: H319; STOT SE 3: H335;	
			Skin Irrit. 2: H315; Aquatic Chronic 2:	
			H411	

NAPHTHALENE - REACH registered number(s): COMPLIANT

202-049-5	91-20-3	-	Carc. 2: H351; Acute Tox. 4: H302;	<1%
			Aquatic Chronic 1: H410; Aquatic Acute	
			1: H400	

Section 4: First aid measures



PC VENTIL-CLEANER

Page: 3

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.



PC VENTIL-CLEANER

Page: 4

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Non-classified ingredients:

HYDROCARBONS, C11-14,N-ALKANES, ISOALKANES, CYCLICS, <2%AROMATICS [DISTILLATES (PETROLEUM), HYDROTREATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1200 mg/m³	-	-	-

1,2,4-TRIMETHYLBENZENE

DNEL/PNEC Values

Hazardous ingredients:

KEROSINE - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.

Туре	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	12,5 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	151 mg/m³	Workers	Systemic
DNEL	Dermal (repeated dose)	7,5 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	32 mg/m³	Consumers	Systemic
DNEL	Oral (repeated dose)	7,5 mg/kg bw/day	Consumers	Systemic

2-ETHYL-1-HEXANOL

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	106,4 mg/m³	Workers	Local
DNEL	Dermal (repeated dose)	23 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	53,2 mg/m³	Workers	Systemic



PC VENTIL-CLEANER

Page: 5

DNEL	Inhalation	53,2 mg/m³	Consumers	Local
DNEL	Dermal (repeated dose)	11,4 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	2,3 mg/m³	Consumers	Systemic
DNEL	Oral (repeated dose)	1,1 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	12,8 mg/m³	Workers	Systemic
DNEL	Inhalation (repeated dose)	26,6 mg/m³	Consumers	Local
DNEL	Inhalation	26,6 mg/m³	Consumers	Local

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids.

Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 2,5

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 175-220 Flammability limits %: lower: 0,6

upper: 7,0 Flash point°C: 64

Autoflammability°C: 200 Vapour pressure: 80mbar

Relative density: 0,798 VOC g/l: 798

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.



PC VENTIL-CLEANER

Page: 6

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBON MIX C10-C13, <0,1% BENZENE

DERMAL	RBT	LD50	>5000	mg/kg
GASES	RAT	1H LC50	>4,951	mg/l
ORAL	RAT	LD50	>5000	mg/kg

KEROSINE - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.

DERMAL	RBT	LD50	>2	mL/kg
ORL	RAT	LDLO	5	ml/kg
VAPOURS	RAT	4H LC50	>590	mg/m³

2-ETHYL-1-HEXANOL

DERMAL	RAT	LD50	>3000	mg/kg
DUST/MIST	RAT	4H LC50	5	mg/l
ORAL	RAT	LD50	2047	mg/kg
VAPOURS	RAT	4H LC50	>0,89	mg/l

Non-classified ingredients:

HYDROCARBONS, C11-14,N-ALKANES, ISOALKANES, CYCLICS, <2%AROMATICS [DISTILLATES (PETROLEUM), HYDROTREATED LIGHT]

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg



PC VENTIL-CLEANER

Page: 7

VAPOURS RAT 8H LC50	>5000 mg/m³
---------------------	-------------

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

NAPHTHALENE

ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	490	mg/kg
SKN	RAT	LD50	>2500	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBON MIX C10-C13, <0,1% BENZENE

ALGAE	72H ErC50	1000	mg/l
Daphnia magna	48H EC50	1000	mg/l
Oncorhynchus mykiss	96H LC50	1000	mg/l

2-ETHYL-1-HEXANOL

ALGAE	72H ErC50	11,5	mg/l
DAPHNIA	48H EC50	39	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.



PC VENTIL-CLEANER

Page: 8

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Use principally as a fuel or other means to generate energy. Solvent

reclamation/regeneration.

Waste code number: 070704

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.



PC VENTIL-CLEANER

Page: 9

H351: Suspected of causing cancer ({{{0|||message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(_)? EXP_ROUTE_.+}}}).

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.