



SAFETY DATA SHEET
PROFI-CAR DIESEL WINTER FIT

Page: 1

Compilation date: 24.11.2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PC DIESEL WINTER FIT (UFI:MRGC-35HN-900K-UKDS)

Product code: 60122

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: additiv liquid

1.3. Details of the supplier of the safety data sheet

Company name: PROFI-TECH GmbH

Otto-Lilienthal-Strasse 2

Friedrichshafen

88046

Germany

Tel: +49 7541 402860

Fax: +49 7541 4028699

Email: info@profi-tech.com

1.4. Emergency telephone number

Emergency tel: 24-hour emergency contact number out side USA/Canada: + 49 70024112112 (PRT)
24-hour emergency contact number in side USA/Canada: +11 49 70024112112 (PRT)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Aquatic Chronic 3: H412; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS08: Health hazard



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P273: Avoid release to the environment.

[cont...]



SAFETY DATA SHEET

PROFI-CAR DIESEL WINTER FIT

Page: 2

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBON, C10-C13, N-ALKANE, ISO-ALKANE, CYCLIC, < 2% AROMATICS, - REACH registered number(s): 01-2119457273-39-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
918-481-9	64742-48-9	-	Asp. Tox. 1: H304; -: EUH066	70-90%

HYDROCARBONS C10, AROMATICS, <1% NAPHTALENE, [SOLVENT NAPHTA (PETROLEUM), HEAVY AROM.] - REACH registered number(s): 01-2119463583-34

918-811-1	1189173-42-9	-	STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; -: EUH066	1-10%
-----------	--------------	---	--	-------

NAPHTHALENE - REACH registered number(s): COMPLIANT

202-049-5	91-20-3	-	Carc. 2: H351; Acute Tox. 4: H302; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
-----------	---------	---	---	-----

Non-classified ingredients:

1,2,4-TRIMETHYLBENZENE - REACH registered number(s): COMPLIANT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]



SAFETY DATA SHEET

PROFI-CAR DIESEL WINTER FIT

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

[cont...]



SAFETY DATA SHEET

PROFI-CAR DIESEL WINTER FIT

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Non-classified ingredients:

1,2,4-TRIMETHYLBENZENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	125 mg/m ³	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

HYDROCARBONS C10, AROMATICS, <1% NAPHTHALENE, [SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.]

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	12,5 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	151 mg/m ³	Workers	Systemic
DNEL	Dermal (repeated dose)	7,5 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	32 mg/m ³	Consumers	Systemic
DNEL	Oral (repeated dose)	7,5 mg/kg bw/day	Consumers	Systemic

NAPHTHALENE

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	3,57 mg/kg, bw/d	Workers	Systemic
DNEL	Inhalation (repeated dose)	25 mg/m ³	Workers	Systemic
DNEL	Inhalation (repeated dose)	25 mg/m ³	Workers	Local
PNEC	Fresh water	2,4 µg/l	-	-
PNEC	Marine water	2,4 µg/l	-	-
PNEC	Microorganisms in sewage treatment	2,9 mg/l	-	-
PNEC	Fresh water sediments	0,0672 mg/kg	-	-
PNEC	Marine sediments	0,0672 mg/kg	-	-
PNEC	Soil (agricultural)	0,0533 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

[cont...]



SAFETY DATA SHEET

PROFI-CAR DIESEL WINTER FIT

Page: 5

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: The floor of the storage room must be impermeable to prevent the escape of liquids.
Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Off-white

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 7,8

Viscosity test method: Kinematic viscosity in 10-6 m²/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 156-280

Melting point/range°C: -19

Flammability limits %: lower: 0,6

upper: 7,0

Flash point°C: 65

Autoflammability°C: 240

Relative density: 0,83

VOC g/l: 783,8

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

[cont...]

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBON, C10-C13, N-ALKANE, ISO-ALKANE, CYCLIC, < 2% AROMATICS,

DERMAL	RBT	LD50	>5000	mg/kg
GASES	RAT	1H LC50	>4,951	mg/l
ORAL	RAT	LD50	>5000	mg/kg

HYDROCARBONS C10, AROMATICS, <1% NAPHTHALENE, [SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.]

DERMAL	RBT	LD50	>2	mL/kg
ORAL	RAT	4H LC50	>590	mg/m ³
ORAL	RAT	LDLO	5	ml/kg

NAPHTHALENE

ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	490	mg/kg
SKN	RAT	LD50	>2500	mg/kg

Non-classified ingredients:

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity



SAFETY DATA SHEET

PROFI-CAR DIESEL WINTER FIT

Page: 7

Hazardous ingredients:

HYDROCARBON, C10-C13, N-ALKANE, ISO-ALKANE, CYCLIC, < 2% AROMATICS,

ALGAE	72H ErC50	1000	mg/l
Daphnia magna	48H EC50	1000	mg/l
Oncorhynchus mykiss	96H LC50	1000	mg/l

HYDROCARBONS C10, AROMATICS, <1% NAPHTALENE, [SOLVENT NAPHTA (PETROLEUM), HEAVY AROM.]

ALGAE	72H ErC50	1-3	mg/l
DAPHNIA	48H EC50	3-10	mg/l
FISCH	96H LC50	2-5	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Use principally as a fuel or other means to generate energy. Solvent reclamation/regeneration.

Waste code number: 130703

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

[cont...]



SAFETY DATA SHEET
PROFI-CAR DIESEL WINTER FIT

Page: 8

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer ({{{0|||message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(_)?EXP_ROUTE_.+}}}).

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.