

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **PROFI-CAR COCKPIT FOAM**
- **Article number:** PROT866024
- **UFI:** CFUV-A57M-000D-XDNJ
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Cleaning material/ Detergent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
PROFI-TECH GmbH
Otto-Lilienthal-Straße 2
88046 Friedrichshafen
Deutschland +49 7541 402860
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number:**
24-hour emergency contact number out side USA/Canada: + 49 70024112112 (PRT)
24-hour emergency contact number in side USA/Canada: +11 49 70024112112 (PRT)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY

(Contd. of page 1)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P280 Wear eye protection / face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards
Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	>25–≤50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-XXXX	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≥10–<20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-XXXX	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	≥1–≤10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-XXXX	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1–≤5%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-XXXX	2-butoxyethanol ⚠ Acute Tox. 3, H331; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	0.1–≤1%
CAS: 137-16-6 EINECS: 205-281-5	Sodium N-lauroylsarcosinate ⚠ Acute Tox. 2, H330; ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315	≥0.1–<1%
CAS: 1336-21-6 EINECS: 215-647-6 Index number: 007-001-01-2 Reg.nr.: 01-2119982985-XXXX	ammonia ⚠ Skin Corr. 1B, H314; ⚠ STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT SE 3; H335: C ≥ 5%	≥0.1–<1%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥5 - <15%
anionic surfactants	<5%
ISOPROPYL ALCOHOL	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: **PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY**

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: **PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY**

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

CAS: 111-76-2 2-butoxyethanol

WEL	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 123 mg/m ³ , 25 ppm Sk, BMGV
-----	---

· DNELs

CAS: 67-63-0 propan-2-ol

Oral	Long Term Systemic Effects	26 mg/kg bw/day (Consumers)
Dermal	Long Term Systemic Effects	319 mg/kg bw/day (Consumers)
		888 mg/kg bw/day (Workers)
Inhalative	Long Term Systemic Effects	89 mg/m ³ (Consumers)
		500 mg/m ³ (Workers)

CAS: 111-76-2 2-butoxyethanol

Oral	Acute Systemic Effects	26.7 mg/kg bw/day (Consumers)
	Long Term Systemic Effects	6.3 mg/kg bw/day (Consumers)
Dermal	Acute Systemic Effects	89 mg/kg bw/day (Consumers)
		89 mg/kg bw/day (Workers)
Inhalative	Long Term Systemic Effects	75 mg/kg bw/day (Consumers)
		125 mg/kg bw/day (Workers)
	Akute Local Effects	147 mg/m ³ (Consumers)
		246 mg/m ³ (Workers)
	Acute Systemic Effects	426 mg/m ³ (Consumers)
		1,091 mg/m ³ (Workers)
	Long Term Systemic Effects	59 mg/m ³ (Consumers)
		98 mg/m ³ (Workers)

· PNECs

CAS: 67-63-0 propan-2-ol

	Fresh Water	140.9 mg/l (Fresh Water)
	Marine Water	140.9 mg/l (Marine Water)
	Fresh Water Sediments	552 mg/kg (Fresh Water Sediments)
	Marine Water Sediments	552 mg/kg (Marine Water Sediments)
	Microorganismus in Sewage Treatment	2,251 mg/l (Microorganismus in Sewage Treatment)
	Soil (Agricultural)	28 mg/kg (Soil (Agricultural))

CAS: 111-76-2 2-butoxyethanol

Inhalative	LC0 (Female, 1h, Steam)	>3.1 mg/l (Guinea Pig)
	LC0 (male, 1h, Steam)	>3.4 mg/l (Guinea Pig)
	EC0 16h	700 mg/l (Bacteria)
	Fresh Water	8.8 mg/l (Fresh Water)
	Marine Water	0.88 mg/l (Marine Water)
	Fresh Water Sediments	34.6 mg/kg (Fresh Water Sediments)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY

(Contd. of page 4)

Marine Water Sediments	3.46 mg/kg (Marine Water Sediments)
Microorganismus in Sewage Treatment	463 mg/l (Microorganismus in Sewage Treatment)
Soil (Agricultural)	2.33 mg/kg (Soil (Agricultural))
Sporadic Release	26.4 mg/l (Sporadic Release)

Ingredients with biological limit values:
CAS: 111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: butoxyacetic acid

· **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Filter A/P2

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material** Value for the permeation: Level ≤ 4 h

· **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Neoprene gloves

· **Eye/face protection**



Tightly sealed goggles

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: **PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY**

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Aerosol
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.5 Vol %
· Upper:	10.9 Vol %
· Flash point:	Not applicable, as aerosol.
· Decomposition temperature:	Not determined.
· pH at 20 °C	10.64
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.968 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	Dichte bezieht sich auf den Wirkstoff
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	16–<33.5 %
· Water:	40.0 %
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: **PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY**

(Contd. of page 6)

· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h	>4.92 mg/l
------------	----------	------------

CAS: 7732-18-5 water, distilled, conductivity or of similar purity

Oral	LD50	>89,800 mg/kg (rat)
------	------	---------------------

CAS: 67-63-0 propan-2-ol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50/6h	>25 mg/l (rat)

CAS: 111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,414 mg/kg (Guinea Pig) (OECD 401) 1,480 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (Guinea Pig) (OECD 402) 400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Serious eye damage/irritation** Causes serious eye irritation.

- **Additional toxicological information:**

CAS: 111-76-2 2-butoxyethanol

Oral	NOAEL (90d) (OECD 408)	<82 mg/kg bw/day (rat male) (OECD 408) >150 mg/kg bw/day (rat, female) (OECD 408)
Dermal	NOAEL (90d) (OECD 411)	mg/kg bw/day (Fish) (OECD 411) 150 mg/kg bw/day (rab)
	NOAEC 90d	<31 ppm (rabbit) (OECD 411)
Inhalative	NOAEC (14week, 5day/week)	62.5 ppm (rat, female) (OECD 413)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY

(Contd. of page 7)

LOAEL (102w, 5 day/w) (OECD 453)	152 mg/m ³ (rat) (OECD 453)
NOAEC (rat, inhalation, 2 year) (OECD 451)	125 ppm (rat) (OECD 451)

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 111-76-2 2-butoxyethanol

LC50 96h (OECD 203)	1,474 mg/l (Fish) (OECD 203)
LC50 48h	1,550 mg/l (daphnia)
LC0 (96h) (OECD 203)	150 mg/l (rab) (OECD 203)
EC50 48h (OECD 202)	1,550 mg/l (daphnia) (OECD 202)
EC50 72h (OECD 201)	1,840 mg/l (Pseudokirchneriella subcapitata)
NOEC, 21d (OECD 211)	100 mg/l (daphnia) (OECD 211)
NOEC 72h (OECD 201)	286 mg/l (Algae) (OECD 201)
NOEL (21d) (OECD 204)	>100 mg/l (Fish) (OECD 204)
log Kow	0.81 / (25°C, pH
BCF, no Bioakumulation	3.16

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

GB

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022



Version number 1.0

Revision: 23.11.2022

Trade name: **PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY**

(Contd. of page 8)

SECTION 14: Transport information

· 14.1 UN number or ID number	UN1950
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
· IMDG	AEROSOLS
· IATA	Aerosols, flammable
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code): -	
· EMS Number:	F-D,S-U
· Segregation groups	(SGG18) Alkalis
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Segregation Code	
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY

(Contd. of page 9)

· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 2: Acute toxicity – Category 2
- Acute Tox. 3: Acute toxicity – Category 3

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2022

Version number 1.0

Revision: 23.11.2022

Trade name: PROFI-CAR COCKPIT FOAM, COCKPIT-SCHAUM SPRAY

(Contd. of page 10)

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB