

according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

53300 - performance 4T SAE 20W-50

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture Motor oil multigrade Uses advised against No information available. 1.3. Details of the supplier of the safety data sheet Company name: **PROFI-TECH GmbH** Street: Otto-Lilienthal-Straße 2 Place: D-88046 Friedrichshafen Telephone: 07541 / 40286 - 0 Telefax: 07541 / 40 286 - 99 info@profi-tech.com e-mail: 1.4. Emergency telephone 24-hour emergency contact number out side USA/Canada: + 49 70024112112 (PRT) number: 24-hour emergency contact number in side USA/Canada: +11 49 70024112112 (PRT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Avoid release to the environment.

Dispose of contents / container in accordance with official regulations.

Special labelling of certain mixtures

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

2.3. Other hazards

EUH208

P273

P501

Endocrine disrupting properties: phenol, dodecyl-, branched. No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

Page 2 of 11

Hazardous components

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	GHS Classification				
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts			0 - < 0,5 %	
	682-816-2				
	Skin Sens. 1, Aquatic Chronic 4; H317 H413				
121158-58-5	phenol, dodecyl-, branched		0 - < 0,15 %		
	310-154-3	604-092-00-9	01-2119513207-49		
	Repr. 1B, Skin Corr. 1C, Eye Dam. H400 H410	1, Aquatic Acute 1, Aquatic Chronic	1; H360F H314 H318		

Full text of H and EUH statements: see section 16.

Specific Con	specific Conc. Limits, M-factors and ATE				
CAS No	EC No	Chemical name	Quantity		
	Specific Conc. I	imits, M-factors and ATE			
121158-58-5	310-154-3	phenol, dodecyl-, branched	0 - < 0,15 %		
	dermal: LD50 = ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10				

Further Information

This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.

Do not leave affected person unattended.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air. Call a doctor if you feel unwell.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

Page 3 of 11

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

- Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire may be liberated:

- Nitrogen oxides (NOx)

- Carbon monoxide (CO)

- Carbon dioxide (CO2).

- Pyrolysis products, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Use of protective clothing In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep people at a distance and stay on the windward side. Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear protective gloves/protective clothing and eye/face protection.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation. Remove from the water surface (e.g. skimming, sucking).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of oil dust. Use personal protection equipment.



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

Do not put any product-impregnated cleaning rags into your trouser pockets. Clear spills immediately.

Advice on protection against fire and explosion

No special fire protection measures are necessary. Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Floors should be impervious, resistant to liquids and easy to clean.

Hints on joint storage

Do not store together with:

- Materials capable of ignition under almost all normal temperature conditions

- Explosives

7.3. Specific end use(s)

Motor oil multigrade

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
121158-58-5	phenol, dodecyl-, branched			
Worker DNEL	, acute	inhalation	systemic	44,18 mg/m ³
Worker DNEL	, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL	, acute	dermal	systemic	166 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	0,79 mg/m³
Consumer DN	IEL, acute	inhalation	systemic	13,26 mg/m ³
Consumer DN	IEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DN	IEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DN	IEL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DN	IEL, acute	oral	systemic	1,26 mg/kg bw/day

Page 4 of 11



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

Page 5 of 11

PNEC values

CAS No	Substance		
Environmenta	l compartment	Value	
121158-58-5	phenol, dodecyl-, branched		
Freshwater		0,000074 mg/l	
Freshwater (ir	ntermittent releases)	0,00037 mg/l	
Marine water		0,000007 mg/l	
Freshwater se	ediment	0,226 mg/kg	
Marine sedime	ent	0,027 mg/kg	
Secondary po	isoning	4 mg/kg	
Micro-organisms in sewage treatment plants (STP)		100 mg/l	
Soil		0,118 mg/kg	

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

When using do not eat, drink, smoke, sniff.

Eye/face protection

During filling, metering, mixing and sampling must be used: Wear eye/face protection. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Recommended glove articles: EN ISO 374

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration. Breakthrough time: > 8h

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:

Liquid



Safety Data Sheet

according to UK REACH Regulation

	53300 - performance 4T SAE 20W-50	
Revision date: 12.07.2021		Page 6 of 11
Colour: Odour: Odour threshold:	yellow - brown characteristic not determined	
pH-Value:	not determined	
Changes in the physical state Melting point/freezing point: Boiling point or initial boiling point and boiling range:	not determined not determined	
Pour point:	-33 °C	
Flash point:	210 °C	
Flammability Solid/liquid:	not applicable not applicable	
Explosive properties Product is not explosive. However, fo	prmation of explosive air/vapour mixtures are possible.	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Self-ignition temperature Solid: Gas:	not applicable not applicable	
Decomposition temperature:	not determined	
Oxidizing properties The product is not: oxidising.		
Vapour pressure:	not determined	
Density (at 15 °C):	0,881 g/cm³	
Water solubility:	not determined	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	
Viscosity / kinematic: (at 40 °C)	150,5 mm²/s	
Relative vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		
Solid content:	not determined	

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

10.4. Conditions to avoid

Avoid: Thermal decomposition



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

10.5. Incompatible materials

- Materials to avoid:
 - Oxidising agent
 - Reducing agent

10.6. Hazardous decomposition products

Hazardous combustion products:

- Nitrogen oxides (NOx)
- Carbon monoxide (CO)
- Carbon dioxide (CO2)
- Pyrolysis products, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
121158-58-5	phenol, dodecyl-, branched					
		LD50 mg/kg	2100	Rat	Publication (1978)	OECD Guideline 401
		LD50 mg/kg	ca. 15000	Rabbit	Study report (1968)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Page 7 of 11



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
121158-58-5	phenol, dodecyl-, branche	ed					
	Acute fish toxicity	LL50	40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,15	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,037	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,0037	21 d	Daphnia magna (Big water flea)	ECHA Dossier	
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209

12.2. Persistence and degradability

No information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
121158-58-5	phenol, dodecyl-, branched			
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	25%	28	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
121158-58-5	phenol, dodecyl-, branched	7,14

BCF

CAS No	Chemical name	BCF	Species	Source
121158-58-5	phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste

Page 8 of 11



according to UK REACH Regulation

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

		•	
14.1.	UN	number:	

- 14.2. UN proper shipping name:
- 14.3. Transport hazard class(es):
- 14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No

EU regulatory information Authorisations (REACH, annex XIV): Substances of very high concern, SVHC (REACH, article 59): phenol, dodecyl-, branched Restrictions on use (REACH, annex XVII): Entry 3, Entry 30 2004/42/EC (VOC): 0,15 % (1,322 g/l) Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III) (SEVESO III): National regulatory information

Page 9 of 11



Revision date: 12.07.2021

Safety Data Sheet

according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Page 10 of 11

Employment restrictions:

Water hazard class (D):

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). 2 - obviously hazardous to water Causes allergic hypersensitivity reactions.

Skin resorption/Sensitization: 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,13,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50% CLP: Classification, labelling and Packaging REACH: Registration, Evaluation and Authorization of Chemicals GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals **UN: United Nations** DNEL: Derived No Effect Level DMEL: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration ATE: Acute toxicity estimate LL50: Lethal loading, 50% EL50: Effect loading, 50% EC50: Effective Concentration 50% ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration BCF: Bio-concentration factor PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative RID: Regulations concerning the international carriage of dangerous goods by rail ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) EmS: Emergency Schedules MFAG: Medical First Aid Guide ICAO: International Civil Aviation Organization MARPOL: International Convention for the Prevention of Marine Pollution from Ships IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method



according to UK REACH Regulation

53300 - performance 4T SAE 20W-50

Revision date: 12.07.2021

Page 11 of 11

Relevant H and EUH statements (number and full text)	
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)