



ECO-TECH SAE 5W-30

ECO-TECH SAE 5W-30 is a HC-synthetic high-performance low-friction oil for petrol and diesel engines in passenger cars. It is a low-SAP product with reduced low sulphur, ash and phosphorus content. Base oils produced with the latest synthesis technology and carefully chosen innovative high-performance additives help reduce the sulphated ash content and guarantee reliable wear protection and keep the engine clean. The oil also significantly lowers fuel consumption. Excellent cold start behaviour ensures optimum lubrication during the cold start phase. The product provides reliable protection under extreme conditions and high temperatures. ECO-TECH SAE 5W-30 is recommended for use under all operating conditions and helps protect the environment as it reduces harmful emissions. ECO-TECH SAE 5W-30 has been developed for petrol and diesel engines with or without particle filters (DPFs) and can also be used in gas-fuelled passenger cars (CNG/LPG). ECO-TECH SAE 5W-30 prolongs the service life of the exhaust gas aftertreatment system and enhances its performance.

Specification

ACEA C2

Recommended application

PSA B71 2290

FIAT 9.55535-S1

Honda, Mitsubishi, Subaru, Toyota (where required)

Technical data	Unit	Test according	ECO-TECH SAE 5W-30
density at 15°C	Kg/m ³	DIN EN ISO 12185	854
Flammable COC	°C	DIN ISO 2592	234
Pourpoint	°C	DIN ISO 3016	-36
Viscosity 40°C	mm ² /s	DIN 51562-1	63,5
Viscosity 100°C	mm ² /s	DIN 51562-1	10,6
VI		DIN ISO 2909	157
Viscosity -30°C	mm ² /s	DIN 51562-1	6100

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**