



## ENDURANCE SAE 10W-30

ENDURANCE SAE 10W-30 is a semi-synthetic high-performance low-friction engine oil of viscosity class SAE 10W-30. Its base oil composition combines the advantages of modern refinery products with those of synthetic components. The base oil composition and shear resistant VI enhancers ensure that the product retains its specified viscosity properties during the entire lubrication time. The ageing process of this engine oil is well managed over the permissible maximum oil change interval. Antioxidants and cleaning additives prevent deposits, keep pistons and valves clean and protect the engine against cold sludge. The low friction loss in the engine significantly reduces fuel consumption and emissions. Low evaporation loss prevents deposits in valves, sludging and laking, so that pistons and piston ring grooves are kept clean. ENDURANCE SAE 10W-30 is recommended for use in all passenger car engines (petrol or diesel) including models with diesel turbochargers and catalytic converters.

### Specification

ACEA A3/B4  
API SL/CF

### Recommended application

MB 229.1  
VW 505 00  
Toyota  
Jeep

Technical data	Unit	Test according	ENDURANCE SAE 10W-30
density at 15°C	Kg/m <sup>3</sup>	DIN EN ISO 12185	870
Flammable COC	°C	DIN ISO 2592	225
Pourpoint	°C	DIN ISO 3016	-36
Viscosity 40°C	mm <sup>2</sup> /s	DIN 51562-1	75
Viscosity 100°C	mm <sup>2</sup> /s	DIN 51562-1	11,5
VI		DIN ISO 2909	140
TBN	mgKOH/g	DIN ISO 3771	8,5

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

**PROFI-CAR**  
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com  
**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**