



SPEED SAE 15W-40

SPEED SAE 15W-40 is a universal SAE 15W-40 mineral engine oil offering excellent protection against wear and corrosion.

SPEED SAE 15W-40 is recommended for use in diesel and petrol engines according to the manufacturer instructions. The SAE 15W-40 classification makes it suitable for year-round use under Central European weather conditions.

Specification

API SF/CD

Recommended application

Technical data	Unit	Test according	SPEED SAE 15W-40
density at 15°C	Kg/m ³	DIN EN ISO 12185	880
Flammable COC	°C	DIN ISO 2592	232
Pourpoint	°C	DIN ISO 3016	-39
Viscosity 40°C	mm ² /s	DIN 51562-1	96
Viscosity 100°C	mm ² /s	DIN 51562-1	13,3
VI		DIN ISO 2909	144
TBN	mgKOH/g	DIN ISO 3771	6

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**