



## SPEED SAE 20W-50

SPEED SAE 20W-50 is a universal SAE 20W-50 mineral engine oil offering excellent protection against wear and corrosion.

SPEED SAE 20W-50 is recommended for use in diesel and petrol engines according to the manufacturer instructions. The SAE 20W-50 classification makes it suitable for year-round use under Central European weather conditions.

### Specification

API SF/CD

### Recommended application

Technical data	Unit	Test according	SPEED SAE 20W-50
density at 15°C	Kg/m <sup>3</sup>	DIN EN ISO 12185	884
Flammable COC	°C	DIN ISO 2592	254
Pourpoint	°C	DIN ISO 3016	-27
Viscosity 40°C	mm <sup>2</sup> /s	DIN 51562-1	152
Viscosity 100°C	mm <sup>2</sup> /s	DIN 51562-1	16,72
VI		DIN ISO 2909	118
TBN	mgKOH/g	DIN ISO 3771	

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

**powered by Quality.**

**PROFI-CAR**  
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)  
**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**