



## **Xtra-SHIFT 6HP**

Xtra-SHIFT 6HP is a Automatic Transmission Fluid with the following properties:

Excellent quality properties

High load capacity, outstanding wear minimisation

Exceptional friction coefficient consistency

No foaming

Very low evaporation loss

Excellent gear shifting properties at low temperatures

Adapted friction coefficient properties for sports-style gear shifting

Outstanding oxidation and thermal stability

No adverse effect on standard sealing materials

Use instructions:

Specially designed for modern ZF 6-speed automatic transmissions in high-powered vehicles.

ATF 6HP is also suitable for older ZF 5-speed automatic transmissions (ZF 5HP).

Not for use in DCT/DSG- (Double Clutch) or CVT- (Continuously-Automatic) transmissions suitable.

Observe manufacturer instructions!

Colour: not coloured

### **Specification**

#### **Recommended application**

BMW ATF M 1375.4 (8322 0142516)

Bentley Oil PY112995PA

FORD MERCON SP/LV

Hyundai SP-IV

Jaguar Fluid 8432

Land Rover TYK 500050

Maserati Oil 231603

Nissan Matic S

Toyota Type WS

VW / Audi G 055 005 A1/A2/A6

ZF Lifeguardfluid6 (S671 090 255)

**powered by Quality.**

**PROFI-CAR**  
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)

**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**



| Technical data  | Unit               | Test according   | <b>Xtra-SHIFT 6HP</b> |
|-----------------|--------------------|------------------|-----------------------|
| density at 15°C | Kg/m <sup>3</sup>  | DIN EN ISO 12185 | 853                   |
| Flammable COC   | °C                 | DIN ISO 2592     | > 170                 |
| Pourpoint       | °C                 | DIN ISO 3016     | -42                   |
| Viscosity 40°C  | mm <sup>2</sup> /s | DIN 51562-1      | 31                    |
| Viscosity 100°C | mm <sup>2</sup> /s | DIN 51562-1      | 6,1                   |
| VI              |                    | DIN ISO 2909     | 154                   |

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

**powered by Quality.**

**PROFI-CAR**  
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany  
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

**PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**