



DIESEL-POWER-TRUCK MONO-G SAE 50

High-performance single-grade engine oil, high viscosity index, high dirt dispensing capacity, stable lubricant film, excellent cleaning capacity, high thermal stability and excellent wear and corrosion protection.

DIESEL-POWER-TRUCK MONO-G SAE 50 is recommended for use in both diesel and petrol engines with or without turbocharger, such as: Commercial diesel vehicle engines, Stationary diesel engines, Construction machines and agricultural units. In addition, the product can be used in hydraulic systems, hydraulic clutches, gearboxes, torque converters and retarders for which the manufacturer prescribes the use of a high-performance single-grade engine oil.

Specification

ACEA E2
API SJ / CF-4

Recommended application

MB 227.0
MAN M 270
Allison C-4
Caterpillar TO-2
MIL-L-2104 E; MIL-L-46152 E
MTU oiltype 1

Technical data	Unit	Test according	DIESEL-POWER-TRUCK MONO-G SAE 50
density at 15°C	Kg/m ³	DIN EN ISO 12185	899
Flammable COC	°C	DIN ISO 2592	290
Pourpoint	°C	DIN ISO 3016	-21
Viscosity 40°C	mm ² /s	DIN 51562-1	239
Viscosity 100°C	mm ² /s	DIN 51562-1	19,5
VI		DIN ISO 2909	93
TBN	mgKOH/g	DIN ISO 3771	11,8

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**