



EVOLUTION 2T

EVOLUTION 2T is a Semi-synthetic two-stroke engine oil with the following properties:

Semi-synthetic two-stroke engine oil.

Excellent protection against rust, corrosion and wear.

Continuous lubricant film preventing piston seizure and scoring.

Protection against ring clogging.

Residue-free combustion preventing spark arching.

Suitable for use in systems with mixed or separate lubrication.

Environmentally friendly thanks to extra low fume emissions.

Use instructions:

EVOLUTION 2T is a semi-synthetic two-stroke engine oil designed for air-cooled and water-cooled two-stroke engines in cars, motorbikes, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.

Observe manufacturer instructions.

Specification

Recommended application

API TC

ISO-L-EGD

JASO FC

| Technical data | Unit | Test according | EVOLUTION 2T |
|-----------------|--------------------|------------------|--------------|
| density at 15°C | Kg/m ³ | DIN EN ISO 12185 | 872 |
| Flammable COC | °C | DIN ISO 2592 | 123 |
| Pourpoint | °C | DIN ISO 3016 | -33 |
| Viscosity 40°C | mm ² /s | DIN 51562-1 | 67,5 |
| Viscosity 100°C | mm ² /s | DIN 51562-1 | 9,53 |
| VI | | DIN ISO 2909 | 121 |

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**