



performance 2T

Mineral two-stroke engine oil.
Good protection against rust, corrosion and wear.
Continuous lubricant film preventing piston seizure and scoring.
Protection against deposits and spark arching.
Suitable for use in systems with mixed or separate lubrication.
Environmentally friendly thanks to low fume emissions.

performance 2T is a universal two-stroke engine oil for air and water cooled two-stroke engines in small motorbikes, scooters and mopeds with separate or mixed lubrication, up to a mixing ratio of 1:50.
Observe manufacturer instructions.

Specification

API TC
ISO-L-EGB
JASO FB

Recommended application

| Technical data | Unit | Test according | performance 2T |
|-----------------|--------------------|------------------|----------------|
| density at 15°C | Kg/m ³ | DIN EN ISO 12185 | 878 |
| Flammable COC | °C | DIN ISO 2592 | 141 |
| Pourpoint | °C | DIN ISO 3016 | -24 |
| Viscosity 40°C | mm ² /s | DIN 51562-1 | 63,6 |
| Viscosity 100°C | mm ² /s | DIN 51562-1 | 8,6 |
| VI | | DIN ISO 2909 | 108 |
| TBN | mgKOH/g | DIN ISO 3771 | 1,25 |

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**