

SYNTH-TECH 4T SAE 5W-50

HC-Synthetic high-performance engine oil for four-stroke motorbike engines. Exceptionally effective wear protection Excellent shear stability
Optimised friction properties
Outstanding low-temperature behaviour
Unrivalled detergent/dispersing properties
Also suitable for wet clutches
Effective rust and corrosion protection
Designed for maximum engine protection

SYNTH-TECH 4T SAE 5W-50 is particularly recommended for the lubrication of high-powered four-stroke motorbike engines and offers excellent protection even under extreme operating conditions (racetrack and on-road).

Observe manufacturer instructions.

Specification

API SN JASO MA / MA2

Recommended application

Technical data	Unit	Test according	SYNTH-TECH 4T SAE 5W-50
density at 15°C	Kg/m³	DIN EN ISO 12185	855
Flammable COC	°C	DIN ISO 2592	235
Pourpoint	°C	DIN ISO 3016	-42
Viscosity 40°C	mm²/s	DIN 51562-1	110
Viscosity 100°C	mm²/s	DIN 51562-1	18,5
VI		DIN ISO 2909	190
TBN	mgKOH/g	DIN ISO 3771	7

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

