



performance 4T SAE 20W-50

performance 4T SAE 20W-50 is a mineral high-performance engine oil for four-stroke motorbike engines with the following properties:

High wear protection

Excellent shear stability

Optimised friction properties

Unrivalled detergent/dispersing properties

Also suitable for wet clutches

Effective rust and corrosion protection

Designed for maximum engine protection

Use instructions:

performance 4T SAE 20W-50 is particularly recommended for the lubrication of high-powered four-stroke motorbike engines, especially engines that are operating under extreme conditions.

Observe manufacturer instructions.

Specification

Recommended application

API SN

JASO MA / MA2

Technical data	Unit	Test according	performance 4T SAE 20W-50
density at 15°C	Kg/m ³	DIN EN ISO 12185	883
Flammable COC	°C	DIN ISO 2592	> 195
Pourpoint	°C	DIN ISO 3016	-21
Viscosity 40°C	mm ² /s	DIN 51562-1	175
Viscosity 100°C	mm ² /s	DIN 51562-1	19,5
VI		DIN ISO 2909	128
TBN	mgKOH/g	DIN ISO 3771	7,5

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**